

# 892LT/894LT

LEARNING REMOTE CONTROLS



## The Single Remote Control Solution for Gated Communities

The LiftMaster® 2-Button Learning Remote Control (892LT) and 4-Button Learning Remote Control (894LT) deliver best-in-class performance and security. They are designed specifically to offer a single remote control solution for gated communities, allowing the resident homeowner to operate their personal LiftMaster Garage Door Opener as well as their community gate entrance. Both models are easy to program and fully compatible with LiftMaster Security+ 2.0® and Security+® Garage Door Openers, Gate Operators, Commercial Door Operators and Commercial Receivers.

### Performance

- **Independent button programming** allows for different frequency and codes: Security+ 2.0 (Tri-band 310/315/390 MHz), Security+ 315 MHz and Security+ 390 MHz.
- **Eliminates the need for multiple remotes** when operating LiftMaster Garage Door Openers, Gate Operators, Commercial Door Operators, or MyQ® Accessories.
- **Cloning capability** of existing LiftMaster DIP Switch Remote Controls (61LM and 361LM) or a LiftMaster Encrypted DIP Switch Remote Control (811LM) to any button.

### Safety and Security

- **Security+ 2.0** rolling code technology virtually eliminates radio interference and offers enhanced range, security and dependability.
- **Security+** rolling code technology with every click a new code is sent.

### Compatible Accessories:



#### Security+ 2.0 Universal Receiver (850LM)

Three channel commercial receiver provides enhanced range, security and dependability. Compatible with all Security+ 2.0 Remote Controls.



#### Security+ 2.0 Weatherproof Universal Receiver (860LM)

Three channel commercial receiver provides enhanced range, security and dependability in a weather-tight housing for extra protection. Compatible with all Security+ 2.0 Remote Controls.



#### Security+ 2.0 Commercial High Capacity Receiver (STAR1000)

High capacity commercial receiver provides enhanced range, security and dependability. Holds up to 1,000 Security+ 2.0 Remote Controls. Compatible with all Security+ 2.0 Remote Controls.



#### Security+ 2.0 Single-Button Encrypted DIP Switch Remote Control (811LM)

Single button visor remote control programs directly to the Security+ 2.0 gate operator receiver for master access and used to clone to the learning remote controls for the gate access.



#### DIP Switch Remote Controls (61LM/361LM)

Single button visor remote controls in 390MHz and 315MHz frequencies. Programs directly to an existing LiftMaster commercial receiver for master access and used to clone to the learning remote control for gate access.

# 892LT/894LT

LEARNING REMOTE CONTROLS

## SPEC SHEET

### STANDARD SPECIFICATIONS

#### DIMENSIONS

- 3.2 in. L x 1.75 in. x 0.7 in. H

#### CARTON

Dimensions:

- Height: 1.13 in.
- Width: 2.75 in.
- Length: 4.75 in.
- Weight: 0.10 lbs.

Contents:

- 1 Remote Control
- 1 visor clip
- 1 instruction sheet

892LT/894LT DIMENSIONS



#### TECHNICAL SPECIFICATIONS

Direct Frequency Capability:	Security+ 2.0® (Tri-Band 310/315/390 MHz) Security+® 315 MHz Security+ 390 MHz
Clone Capability:	811LM, 361LM, 61LM
Operating Temp Range:	-40°C to +65°C @ 50% Rh; -40°F to +149°F @ 50% Rh
Storage/Ship Temp Range:	-40°C to +85°C @ 50% Rh
Battery (included):	AAA Battery
Battery Life:	Up to 3 years

#### COMPATIBILITY

Code / Frequency for Direct Programming:

- Security+ 2.0 (310/315/390 MHz Tri-Band) - Default
- Security+ 315 MHz
- Security+ 390 MHz

Code / Frequency for CLONING:

- |                                          |       |
|------------------------------------------|-------|
| - Encrypted DIP Switch (310/315/390 MHz) | 811LM |
| - DIP Switch 315 MHz                     | 361LM |
| - DIP Switch 390 MHz                     | 61LM  |

#### WARRANTY

One year limited warranty.